

Multi-functional, water displacing rust preventative and lubricant

Description

MOLYSLIP COMBAT spray is an advanced water-displacing fluid which deposits a protective and lubricating film. The petroleum base is reinforced with sophisticated performance additives that bind to metal surfaces protecting them from friction, wear and atmospheric corrosion.

COMBAT is designed as a true multi-purpose product that will displace moisture from surfaces, lubricate, protect from corrosion and act as a penetrating and releasing agent for sized and corroded parts. COMBAT is free from silicones, is non-staining and suitable for use on most metals. The product is compatible with most commonly encountered plastics and rubbers.

Features and benefits

- Actively displaces moisture from surfaces
- Effective protection against corrosion
- Excellent penetration and release properties
- All-round multi-purpose lubricant

Packaging

400ml aerosol / 5 Litre / 205 Litre

Technical data

Combat



Instructions for use

Aerosol

Shake well, hold can upright and spray from a distance of approximately 15-30cm.

Bulk Fluid

Supplied ready for use for spray, dip or brush application.

Technical data (typical values)

Property	Test method	Result
Appearance	-	Pale brown liquid
Film thickness	-	0.005 μ
Operating temperature range	-	-50°C to + 140°C

Storage

Store MOLYSLIP COMBAT spray of direct sunlight.

Storage temperature should be controlled to between 5°C and 35°C.

The product information in this publication is based on knowledge and experience at the time of printing. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.
Issue date 05-21

Molyslip Atlantic Limited, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK
Tel: +44 (0)161 804 4700 Fax: +44 (0)161 804 4701 enquiries@molyslip.co.uk www.molyslip.co.uk

Company registration number: 02664511; Company registered in England VAT registration number GB578295191