

Technical data

ECOSLIP OCTG

Metal Free Tool Joint & Drill Collar Compound

Description

MOLYSLIP ECOSLIP OCTG is a premium performance, metal-free, tool joint & drill collar compound based on highly quality vegetable oil thickened with a soap matrix. The product contains specially selected solid lubricants coupled with high levels of corrosion inhibitors, anti-oxidant and anti-wear additives that make the product particularly suitable for use under the most aggressive conditions in corrosive wet/humid, dirty or chemical environments where a high degree of water washout resistance is required.

MOLYSLIP ECOSLIP OCTG has excellent lubricating and anti-wear properties to reduce friction during assembly preventing galling, 'pick-up' and seizure facilitating consistent joint make-up and easier breakout for routine maintenance. The product is formulated to meet the requirements of *API RP 5A3 / ISO 13678:2010.

MOLYSLIP ECOSLIP OCTG is effective over a wide temperature range and is specifically designed to prevent seizure of threaded connections and 'cold welding' of rotary shoulder/drill collar/tool joint connections on oilfield equipment such as drill strings, casings, production tools and tubing etc. The specially formulated blend of additives provides enhanced adhesion to cold/wet tooling and a high resistance to wash off whilst being thermally stable making it suitable for use in applications where high temperatures are encountered.

MOLYSLIP ECOSLIP OCTG is biodegradable and compliant with the requirements of HOCNF 'E' classification in the UK/NL and 'Yellow' rating in Norway.

*API RP 5A3/ISO13678:2010 – "Petroleum and natural gas industries-evaluation and testing of thread compounds for use with casing, tubing, line pipe and drill stem elements".


Features and benefits

- Low sulphur content
- Brushable at low temperature (down to -18°C)
- Excellent load carrying and anti-wear properties
- Allows consistent joint make-up
- Highly effective protection against corrosion
- Outstanding resistance to water washout
- Can be applied to cold, damp equipment
- Effective over a wide temperature range (-20°C to +140°C)

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@moly Slip.co.uk www.moly Slip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927



Technical data

ECOSLIP OCTG

Metal Free Tool Joint & Drill Collar Compound

Instructions for use

MOLYSLIP ECOSLIP OCTG should be applied manually by brush to clean, degreased and dry (where possible) tool joint threads and shoulders.

For best results apply to both mating surfaces.

Storage

MOLYSLIP ECOSLIP OCTG should be stored in original, unopened packaging, out of direct sunlight at temperatures between 5°C and 35°C. The most up to date shelf life information for Molyslip products can be found on the certificate of analysis issued at the time of manufacture.

Packaging and product code

Code	Pack
M802020	20kg pail

Technical data

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@molyslip.co.uk www.molyslip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927

Technical data

ECOSLIP OCTG

Metal Free Tool Joint & Drill Collar Compound

Property	Test method	Result
Appearance	-	Grey/black paste
Worked penetration	IP50	310-340
NLGI Classification	-	1
Drop point	IP396	>140°C
SG (kg/l)	-	1.2
Corrosion resistance (EMCOR)	IP220	0:0
Base oil viscosity	IP71	300cSt
Solids content	-	> 40%
4-ball weld load	IP239	500kg
Friction factor	API Mod	08
Service rating	-	-20°C up to +140°C

Note: These values are typical only and do not constitute a specification

*The Friction Factor is a 'relative' number, many operational variables such as pipe size, thread type / geometry, drilling muds and extraneous contamination, etc. affect the friction factor. In all instances experience and prior application knowledge should be used to adjust make-up torque accordingly. If in doubt, contact the drill pipe manufacturer for torque and friction- related specifications.

Limited warranty information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. We accept no liability for any loss and/or damage arising from a failure to store our products in accordance with the information contained in this technical sheet.

Metalube Group's sole warranty is that our products will meet their quality control specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

To the fullest extent permitted by applicable law, Metalube Group specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Metalube Group disclaims liability for any incidental or consequential damages.

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@moly Slip.co.uk www.moly Slip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927