

Technical data

OCL-F25

Fully synthetic chain lubricant

Description

MOLYSLIP OCL-F25 is a fully synthetic lubricant that has been specifically formulated to meet the demands of lubricating chains operating in a wide variety of industrial and food production environments. It is formulated from the very latest technology synthetic base oils, polymeric viscosity improvers, antioxidants, anti-wear additives and unique rust inhibitors.

This unique combination delivers outstanding corrosion protection in high humidity environments (for example prowers) whilst maintaining excellent low temperature properties and the ability to operate at temperatures up to 240°C.

The formulation is fully compliant with NSF H1 requirements for lubricants with incidental food contact.

Features and benefits

- Superb oxidation stability allows high temperature use
- Excellent corrosion protection in high humidity environments
- Low evaporation rate extends relubrication intervals
- Good anti-wear properties protect chain and drive system components
- Meets the requirements of NSF H1

Instructions for use

MOLYSLIP OCL-F25 should be used as supplied.

Lubrication systems should ideally be drained and flushed prior to introduction of OCL-F25.

Refer to the product safety data sheet for guidance on safe handling, storage and disposal.

Storage

MOLYSLIP OCL-F25 should be stored in original, unopened packaging, out of direct sunlight at temperatures between 5°C and 35°C. The most up to date shelf life information for MOLYSLIP products can be found on the certificate of analysis issued at the time of manufacture.

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@molyslip.co.uk www.molyslip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927

Technical data

OCL-F25

Fully synthetic chain lubricant

Packaging and product codes

Code	Pack
M432155	5 Ltr
M432120	20 Ltr

Technical data

Property	Test method	Grade
Appearance	MSTM 1	Clear/yellow fluid
Base fluid type	-	Synthetic
Kinematic Viscosity at 40°C	MSTM 27	220 cSt
Kinematic Viscosity at 100°C	MSTM 27	21 cSt
Density at 20°C	MSTM 23	0.86 g.cm ⁻³
Viscosity Index	ISO 2909	113
Noack Evaporation Loss	MSTM 91	1.9%
Operating temperature	-	-30°C to +240°C

Note: These values are typical only and do not constitute a specification

Limited warranty information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. We accept no liability for any loss and/or damage arising from a failure to store our products in accordance with the information contained in this technical sheet.

Metalube Group's sole warranty is that our products will meet their quality control specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

To the fullest extent permitted by applicable law, Metalube Group specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Metalube Group disclaims liability for any incidental or consequential damages.

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@molyslip.co.uk www.molyslip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927